



## ePAQ-9410/9420 Multifunction Gateway

### Bring your Substation Devices up to Full Productivity

**Interface with All Devices Using  
Any Open Protocol and Over Any  
Media**

**Choice of RJ-45 or DB-9 Serial  
Port Connections**

**Redundant Architecture for  
Critical Applications**

**Easy, Modular Expansion for  
Additional Hardware I/O Points**

**Serial Ports May be Configured  
for Rear Panel DB-9 Connectors**

**Security Tools available for  
Meeting latest NERC-CIP and  
Cyber Security Requirements**

**Quick and Easy Configuration  
with Provided CONFIGWIZ®  
Windows Software**

**SD Memory Card and USB Ports  
for Easy, but Secure, User  
Expansion and Update**

**Embedded Web Server and HMI  
for Local or Remote Display and  
Configuration**

The ePAQ-9410/9420 Multifunction Gateways should be at the core of your substation management program for the Smart Grid. Whether serving as an expandable front end for legacy RTUs or as the platform for the next stage of your distribution automation program, the ePAQ-9410/9420 can serve to connect the myriad intelligent devices within your substation to your larger enterprise in a reliable and secure fashion.



### ePAQ-9425 Option with Rear Panel DB-9 Serial Connection.

### Data Concentration for Your Substation Devices

The ePAQ-9410/9420 can integrate the complete catalog of IEDs using our library of legacy or open, industry standard protocols, be they serial or LAN based. In addition to data concentration, the unit can perform custom computations needed for filtering, translating, pre-processing or reduction. With CONFIGWIZ®, raw or processed IED data can be distributed to any remote enterprise, be they SCADA, maintenance or engineering activities through serial or WAN based channels. If needed, such transfers can be encrypted and authenticated for greater security.

# ePAQ Multifunction Gateway

<b>Server Protocols</b>	DNP3 (serial and over IP with secure authentication), Secure FTP, L&G 8979 (Serial and over IP), Modbus (RTU and TCP), QUICS (Serial and over IP), Tejas/Valmet Series III/IV, BETAC, CDC I & II, Conitel, and others		
<b>Client Protocols</b>	DNP3 (serial and over IP with secure authentication), Modbus (RTU and TCP), IEC 61850, SEL Fastmeter/ASCII with device discovery, Large library of legacy SCADA protocols to interface older RTUs to upgraded, open systems and modern communication channels.		
<b>Network and Time Mgt.</b>	SNMP, NTP, PTP (IEC 1588), SNTP, IRIG-B. Supercap backup of internal real-time clock.		
<b>Programmable Logic</b>	Programmable Logic and Communications Controller (PLCC)		
<b>Additional I/O</b>	Secure and configurable HTML display server (local or remote), IED engineering access		
<b>Ports Capacities</b>	<b>ePAQ-9410</b> 3U rack space, front or rear mounted	2-Bell 202T telecom legacy I/O 2-RS-232C (bit or byte) 1-SD/SDHC memory card IRIG-B (BNC, RS 485, serial fiber)	4-RS-232/RS-485 (switchable) 2-USB host ports, 1-USB Maint. Port. 2-100 baseFX Ethernet 4-10/100 baseTX Ethernet (RJ-45)
<b>ePAQ-9425 Option Provides DB-9 Serial Connectors Mounted on the Gateway Rear Panel</b>	<b>ePAQ-9420</b> 3U rack space, front or rear mounted	All ePAQ-9410 features <b>plus:</b>	16-RS-232/RS-485 (switchable) -or- 8-Serial fiber ports (multimode w/STconnectors)
	<b>eXP-9430</b> Add-on expansion 1U rack space, front or rear mounted	Comm Port Expander 1-100 baseFX Ethernet 1-10/100 baseTX Ethernet 1-RS-485:IRIG-B	16-RS-232/RS-485 (switchable) -or- 8-Serial fiber ports (multimode w/STconnectors)
<b>Hardwired I/O</b>	Status: Maximum of 16,384 points at 64 points per I/O interface board Analog: Maximum of 8,192 at 32 points per I/O interface board Control: Maximum of 32,768 at 16 points per I/O interface board (Up to 8 AGC Raise/Lower)		
<b>Architecture</b>	LINUX Real Time O/S. Option for redundant processors and/or communication with auto-failover		
<b>Configuration</b>	Through secure CONFIGWIZ® management program and browser based test panel via local USB maintenance port or local/remote IP connection. Full complement of data filtering, port switching, IED I/O control, and other management/diagnostic functions.		
<b>LED Indicators</b>	Indicators to display CPU health, power, communications, IRIG-B activity, port activity with allowances provided for future indications.		
<b>Power</b>	48-125 Vdc, 120/240/277 Vac (50/60 Hz, +/- 10%)		
<b>Environmental</b>	-40 to +85 degrees centigrade, 5 to 95% humidity (non-condensing)		

## QEI

60 Fadem Road  
Springfield, NJ 07081 USA  
T: +973-379-7400 F: +973-379-2138  
E: [sales@qeinc.com](mailto:sales@qeinc.com)  
W: [www.qeinc.com](http://www.qeinc.com)

This literature is for illustration purposes only, and is not part of any contract. As we have a policy of continuous product improvement, any features may be modified without notice. All trademarks and names mentioned in this document remain the exclusive property of their holder.

V4.2 01/17